North America's Leader in Hazardous Material Information Management

1905 Aston Avenue, Carlsbad, CA 92008 Phone (800) 451-8346 Fax (760) 602-8888

# MSDS PRODUCT INFORMATION

Date: 10/07/2005

To: MSDS Requester

From: 3E Company

Subject: The MSDS you have requested

### [ ] MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communicatin Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

#### [ ] MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

#### [X] MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

#### [ ] MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: DiversiTech Corporation

Product Name: Carbon Dioxide, Gas



## MATERIAL SAFETY DATA SHEET

### SUBSTANCE IDENTITY:

SUBSTANCE: Carbon Dioxide, Gas

CAS #124-38-9

MOLECULAR FORMULA: C-O

CHEMICAL FAMILY: Oxide of Carbon

MOLECULAR WT: 44,01

CERCLA RATINGS (SCALE 0-3): HEALTH#3 FIRE#0 REACTIVITY#0 PERSISTENCE#0

NFPA RATINGS (SCALE 0-4): HEALTH-LI FIRE=0 REACTIVITY=0

### **COMPONENTS AND CONTAMINANTS**

COMPONENT: Carbon Dioxide, Gas (CAS#124-38-9)

OTHER CONTAMINANTS: None

PERCENT: 100.0

### PHYSICAL DATA

DESCRIPTION: Odorless, Colorless Gas, with a Slight Acidic Taste.

BOILING POINT: -109 F (-79 C) (SUBLIMES)
MELTING POINT: -70,6 F (-57 C) @ 4000 mmHg

SPECIFIC GRAVITY: 1,52 @ 21 C

VAPOR PRESSURE: 43700 mmHg @ 21 C

SQLUBILITY IN WATER: Soluble

PH: Acidic in Solution

VAPOR DENSITY: 1.5

SOLVENT SOLUBILITY: Soluble in alcohol, acetone, hydrocarbons, most organic liquids.

VAPOR DENSITY: 1.977 G/1 Ø 750 mmHg and 0 C

### FIRE AND EXPLOSION DATA

FIRE/EXPLOSION HAZARD: GAS-Negligible fire hazard when exposed to heat or flame. CYLINDER-May explode in heat of fire.

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, or halon. For larger fires, use water spray, fog or stand foam.

FIREFIGHTING: Cool fire-exposed cylinders with water from the side until well after the fire is out.

Use agents suitable for type of fire. Cool cylinders with flooding amounts of water, applied from as far a distance as possible.

### **CONDITIONS TO AVOID**

Do not permit physical damage or overheating of cylinders. Contents are under pressure; cylinders may rupture and travel a considerable distance. Contact of liquefied gases with water may cause explosions due to rapid temperature fluctuations.

#### 12 GRAN CO. (É) ARTICLE No. 5406 7.25mm PLAIN NECK Ø8 . 7 .... Ø7.3%% Ø3.2 NET WEIGHT CO. FULLGEWICHT CO. POIDS DE REMPLISSAGE EN CO. 1128 WATER CAPACITY 14.7 m/ MIN CAPACITE EN EAU FILLING DENSTIY FULLFAKTOR FACTEUR DE REMPLISSAGE 82% MAX TEST PRESSURE 250 830.8 PRUFORUCK BAR PRESSION D'ESSAI BURST PRESSURE OF CYLINDER BERSTORUCK DES ZYLINDERS PRESSION D'ECLATEMENTE DU CYLINDER >54D BAR CAP PIERCING FORCE KAPPEN ANSTECHKRAFT FORCE DE PERCUTION 200-240 CO; (E290)- .TSI SPEC. 0197- 99.95% PURITY MARKING PROCESS: MARKING: BESCHRIFTUNG: INSCRIPTION: Ø18.610.1 PACKING: LOOSE, IN CARTONS (0362) OF 450 PCS WY OF CARTON: 19.8 KG CARTON MARKING: CARRON DIOXIDE: 2.2 | UNIO13 & COFYRIGHT TITLE: 12G CO. SPORTS CYLINDER 12G CO. ZYLINDER FUR SPORT BOUTERLE DE 12G CO. POUR SPORTS ral Cobs A-12:10 urus, Listenfragregesta 4 2 97-91-27 | syoul RS These products are the subject of patent \$1-04-14 tayout | 'RS W-NR. 1.0538 DIN 1624 514 SPECIAL DEEP ORAWING STEEL gratuation to suffice, summe and principal Not : countries of the marie. This drawing and git iva.No. Doly change Name interesting or descriptive extine aut aut Surfone Scole OrgNo: 5406 2 Namé Dolthe administrative community and page community and supplies or upon the distriction invested the approximation of the distriction of the supplies of the supp 2 tetok (i) (i) (i) (ii) RS Art Not 5406 95-02-23 2:1 without the prior bye written special Fe/2n5CH This bagile 5406 1 dimensions in mit the public,